

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Revision Date 16.03.2020

Version 18.5

SECTION 1. Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Catalogue No.	100317
Product name	Hydrochloric acid fuming 37% for analysis EMSURE® ACS,ISO,Reag. Ph Eur
REACH Registration Number	This product is a mixture. REACH Registration Number see section 3.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Reagent for analysis, Chemical production In compliance with the conditions described in the annex to this safety data sheet.
-----------------	--

1.3 Details of the supplier of the safety data sheet

Company	Merck KGaA * 64271 Darmstadt * Germany * Phone: +49 6151 72-0
Responsible Department	LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone number **Please contact the regional company representation in your country.****SECTION 2. Hazards identification****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Corrosive to metals, Category 1, H290
Skin corrosion, Category 1B, H314
Specific target organ toxicity - single exposure, Category 3, Respiratory system, H335
For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)***Hazard pictograms*

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

Signal word
Danger

Hazard statements
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.

Precautionary statements
Prevention
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/
physician.

Reduced labelling (≤125 ml)

Hazard pictograms



Signal word
Danger

Hazard statements
H314 Causes severe skin burns and eye damage.

Precautionary statements
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/ physician.

2.3 Other hazards

None known.

SECTION 3. Composition/information on ingredients

Chemical nature Aqueous solution

3.1 Substance

Not applicable

3.2 Mixture

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No.	100317
Product name	Hydrochloric acid fuming 37% for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Hydrogen chloride gas

5.3 Advice for firefighters

Special protective equipment for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Suppress (knock down) gases/vapours/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders: Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills.

Observe possible material restrictions (see sections 7 and 10).

Take up with liquid-absorbent and neutralising material (e.g. Chemisorb® H⁺, Merck Art. No. 101595). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No metal containers.

Storage conditions

Tightly closed.

Recommended storage temperature see product label.

7.3 Specific end use(s)

See exposure scenario in the Annex to this MSDS.

Page 4 of 19

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

Hydrochloric Acid (7647-01-0)

Worker DNEL, acute Local effects inhalation 15 mg/m³

Worker DNEL, longterm Local effects inhalation 8 mg/m³

Predicted No Effect Concentration (PNEC)

Hydrochloric Acid (7647-01-0)

PNEC Fresh water 0,036 mg/l

PNEC Marine water 0,036 mg/l

PNEC Aquatic intermittent release 0,045 mg/l

PNEC Sewage treatment plant 0,036 mg/l

8.2 Exposure controls

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection

Tightly fitting safety goggles

Hand protection

full contact:

Glove material: Nitrile rubber

Glove thickness: 0,11 mm

Break through time: 480 min

splash contact:

Glove material: natural latex

Glove thickness: 0,6 mm

Break through time: 120 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 741 Dermatril® L (full contact), KCL 706 Lapren® (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment

Acid-resistant protective clothing

Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: filter E-(P2)

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Colour	colourless
Odour	stinging
Odour Threshold	0,8 - 5 ppm Gaseous hydrogen chloride (HCl).
pH	< 1 at 20 °C
Solidification point	-30 °C
Boiling point	No information available.
Flash point	Not applicable
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Vapour pressure	190 hPa at 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No.	100317
Product name	Hydrochloric acid fuming 37% for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Relative vapour density No information available.

Density ca.1,19 g/cm³
at 20 °C

Relative density No information available.

Water solubility at 20 °C
soluble

Partition coefficient: n-
octanol/water Not applicable

Auto-ignition temperature No information available.

Decomposition temperature No information available.

Viscosity, dynamic 2,3 mPa.s
at 15 °C

Explosive properties Not classified as explosive.

Oxidizing properties none

9.2 Other data

Ignition temperature Not applicable

Corrosion May be corrosive to metals.

SECTION 10. Stability and reactivity

10.1 Reactivity

Corrosive in contact with metals

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Exothermic reaction with:

Amines, potassium permanganate, salts of oxyhalogenic acids, semimetallic oxides,
semimetallic hydrogen compounds, Aldehydes, vinylmethyl ether

Risk of ignition or formation of inflammable gases or vapours with:

carbides, lithium silicide, Fluorine

Generates dangerous gases or fumes in contact with:

Aluminium, hydrides, formaldehyde, Metals, strong alkalis, Sulphides

Risk of explosion with:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

Alkali metals, conc. sulfuric acid

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

Metals, metal alloys

Gives off hydrogen by reaction with metals.

10.6 Hazardous decomposition products

in the event of fire: See section 5.

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Mixture

Acute oral toxicity

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

Acute inhalation toxicity

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Acute dermal toxicity

This information is not available.

Skin irritation

Mixture causes burns.

Eye irritation

Mixture causes serious eye damage. Risk of blindness!

Sensitisation

This information is not available.

Germ cell mutagenicity

This information is not available.

Carcinogenicity

This information is not available.

Reproductive toxicity

This information is not available.

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure

Mixture may cause respiratory irritation.

Target Organs: Respiratory system

Specific target organ toxicity - repeated exposure

This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

Aspiration hazard

This information is not available.

11.2 Further information

After uptake:

After a latency period:

cardiovascular disorders

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Components

Hydrochloric Acid

Skin irritation

Rabbit

Result: Corrosive

OECD Test Guideline 404

Eye irritation

Rabbit

Result: Irreversible effects on the eye

OECD Test Guideline 405

Sensitisation

Maximisation Test Guinea pig

Result: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

SECTION 12. Ecological information

Mixture

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water

Not applicable

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Substance(s) in the mixture do(es) not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII, or a PBT/vPvB assessment was not conducted.

12.6 Other adverse effects

Additional ecological information

Forms corrosive mixtures with water even if diluted. Harmful effect due to pH shift.

Discharge into the environment must be avoided.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

Components

Hydrochloric Acid

Toxicity to fish

Lepomis macrochirus (Bluegill sunfish): 20,5 mg/l; 96 h
OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

EC50: 1,3 mg/l; 48 h
OECD Test Guideline 202

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

SECTION 13. Disposal considerations

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)

14.1 UN number	UN 1789
14.2 Proper shipping name	HYDROCHLORIC ACID
14.3 Class	8
14.4 Packing group	II
14.5 Environmentally hazardous	--
14.6 Special precautions for user	yes
Tunnel restriction code	E

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

14.1 UN number	UN 1789
14.2 Proper shipping name	HYDROCHLORIC ACID
14.3 Class	8
14.4 Packing group	II
14.5 Environmentally hazardous	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

14.6 Special precautions for user no

Sea transport (IMDG)

14.1 UN number UN 1789
14.2 Proper shipping name HYDROCHLORIC ACID
14.3 Class 8
14.4 Packing group II
14.5 Environmentally hazardous --
14.6 Special precautions for user yes
EmS F-A S-B

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard SEVESO III
Legislation Not applicable

Occupational restrictions Take note of Dir 94/33/EC on the protection of young people at work.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer not regulated

Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC not regulated

Substances of very high concern (SVHC) This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of $\geq 0.1\%$ (w/w).

National legislation

Storage class 8B

15.2 Chemical safety assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

For this product a chemical safety assessment was not carried out.

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.

Training advice

Provide adequate information, instruction and training for operators.

Labelling

Hazard pictograms



Signal word

Danger

Hazard statements

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.

Precautionary statements

Prevention

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P310 IF exposed or concerned: immediately call a POISON CENTER or doctor/physician.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Regional representation

This information is given on the authorised Safety Data Sheet for your country.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

EXPOSURE SCENARIO 1 (Industrial use)

1. Industrial use Reagent for analysis, Chemical production)

Sectors of end-use

- SU 3* Industrial uses: Uses of substances as such or in preparations at industrial sites
SU9 Manufacture of fine chemicals
SU 10 Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)

Chemical product category

- PC19* Intermediate
PC21 Laboratory chemicals

Process categories

- PROC1* Use in closed process, no likelihood of exposure
PROC2 Use in closed, continuous process with occasional controlled exposure
PROC3 Use in closed batch process (synthesis or formulation)
PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises
PROC5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)
PROC8a Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
PROC8b Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC10 Roller application or brushing
PROC14 Production of preparations or articles by tableting, compression, extrusion, pelletisation
PROC15 Use as laboratory reagent

Environmental Release Categories

- ERC1* Manufacture of substances
ERC2 Formulation of preparations
ERC4 Industrial use of processing aids in processes and products, not becoming part of articles
ERC6a Industrial use resulting in manufacture of another substance (use of intermediates)
ERC6b Industrial use of reactive processing aids
-

2. Contributing scenarios: Operational conditions and risk management measures

2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC2, ERC4, ERC6a, ERC6b

Other given operational conditions affecting environmental exposure

Number of emission days per 360

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No.	100317
Product name	Hydrochloric acid fuming 37% for analysis EMSURE® ACS,ISO,Reag. Ph Eur

year	
Remarks	Substance hydrolyses rapidly.

Technical conditions and measures / Organizational measures

Water	Ensure all waste water is collected and treated via a WWTP. Solutions with low pH-value must be neutralized before discharge.
-------	---

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b, PROC15

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 40 %.
Physical Form (at time of use)	High volatile liquid

Frequency and duration of use

Frequency of use	8 hours/day
------------------	-------------

Other operational conditions affecting workers exposure

Outdoor / Indoor	Indoor with local exhaust ventilation (LEV)
------------------	---

Organisational measures to prevent /limit releases, dispersion and exposure

Covers daily exposures up to 8 hours.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Use suitable eye protection.

2.3 Contributing scenario controlling worker exposure for: PROC5, PROC8a, PROC9, PROC10, PROC14

Product characteristics

Concentration of the Substance in Mixture/Article	Covers the percentage of the substance in the product up to 40 %.
Physical Form (at time of use)	High volatile liquid

Frequency and duration of use

Frequency of use	8 hours/day
------------------	-------------

Other operational conditions affecting workers exposure

Outdoor / Indoor	Indoor with LEV and enhanced general ventilation
------------------	--

Organisational measures to prevent /limit releases, dispersion and exposure

Covers daily exposures up to 8 hours.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Use suitable eye protection.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

3. Exposure estimation and reference to its source

Environment

CS	Use descriptor	Msafe	Compartment	RCR	Exposure Assessment Method
2.1			All compartments		Qualitative assessment used to conclude safe use.

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.2	PROC1	longterm, inhalative, local	< 0,01	ECETOC TRA, modified
2.2	PROC2	longterm, inhalative, local	0,19	ECETOC TRA, modified
2.2	PROC3	longterm, inhalative, local	0,38	ECETOC TRA, modified
2.2	PROC4	longterm, inhalative, local	0,76	ECETOC TRA, modified
2.2	PROC8b	longterm, inhalative, local	0,57	ECETOC TRA, modified
2.2	PROC15	longterm, inhalative, local	0,38	ECETOC TRA, modified
2.3	PROC5	longterm, inhalative, local	0,57	ECETOC TRA, modified
2.3	PROC8a	longterm, inhalative, local	0,57	ECETOC TRA, modified
2.3	PROC9	longterm, inhalative, local	0,46	ECETOC TRA, modified
2.3	PROC10	longterm, inhalative, local	0,57	ECETOC TRA, modified
2.3	PROC14	longterm, inhalative, local	0,57	ECETOC TRA, modified

The default parameters and -efficiencies of the applied exposure assessment model were used for the calculation (unless stated differently).

For (other) acute and local effects risk management measures are based on qualitative risk characterisation.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No.	100317
Product name	Hydrochloric acid fuming 37% for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Categories (SPERCs).

For scaling of worker exposure assessments performed with ECETOC TRA, please consult the Merck tool ScIDeEx® at www.merckmillipore.com/scideex.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

EXPOSURE SCENARIO 2 (Professional use)

1. Professional use Reagent for analysis, Chemical production)

Sectors of end-use

SU 22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category

PC21 Laboratory chemicals

Process categories

PROC15 Use as laboratory reagent

Environmental Release Categories

ERC2 Formulation of preparations

ERC6a Industrial use resulting in manufacture of another substance (use of intermediates)

ERC6b Industrial use of reactive processing aids

2. Contributing scenarios: Operational conditions and risk management measures

2.1 Contributing scenario controlling environmental exposure for: ERC2, ERC6a, ERC6b

Other given operational conditions affecting environmental exposure

Number of emission days per year 360

Remarks Substance hydrolyses rapidly.

Technical conditions and measures / Organizational measures

Water Ensure all waste water is collected and treated via a WWTP. Solutions with low pH-value must be neutralized before discharge.

2.2 Contributing scenario controlling worker exposure for: PROC15

Product characteristics

Concentration of the Substance in Mixture/Article Covers the percentage of the substance in the product up to 40 %.

Physical Form (at time of use) High volatile liquid

Frequency and duration of use

Frequency of use 8 hours/day

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor with local exhaust ventilation (LEV)

Organisational measures to prevent /limit releases, dispersion and exposure

Covers daily exposures up to 8 hours.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100317
Product name Hydrochloric acid fuming 37% for analysis EMSURE®
ACS,ISO,Reag. Ph Eur

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Use suitable eye protection.

3. Exposure estimation and reference to its source

Environment

CS	Use descriptor	Msafe	Compartment	RCR	Exposure Assessment Method
2.1			All compartments		Qualitative assessment used to conclude safe use.

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.2	PROC15	longterm, inhalative, local	0,76	ECETOC TRA, modified

The default parameters and -efficiencies of the applied exposure assessment model were used for the calculation (unless stated differently).

For (other) acute and local effects risk management measures are based on qualitative risk characterisation.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

For scaling of worker exposure assessments performed with ECETOC TRA, please consult the Merck tool ScIDeEx® at www.merckmillipore.com/scideex.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.